

Application No.: 09/997,351

Docket No.: JCLA8275

In The Claims:

Please amend claims 1, 5, 6, and 9 as follows:

Claim 1. (currently amended) An optical automatic control encoder, with a diffraction grating, which is immune from an unevenness of a grating surface interval, and has a high tolerance to a alignment error, at least comprising:

a light source, which generates a light beam having a ~~sufficient~~ coherence length;

an optical scale, having ~~a the~~ diffraction grating, used to detect a displacement of an object that is under measured by the optical scale;

12 7 an optical head, which polarizes a single input signal light beam for providing outputs of two parallel light beams each having one linear polarizing state perpendicular to each other, and combines the two parallel light beams into a single output signal light beam, wherein since ~~the a~~ polarizing switch mechanism exists in a beam path, the single input signal light beam and the single output signal light beam are ~~can be~~ shifted in position to apply both an input mechanism and an output mechanism simultaneously, *from what?*

wherein the optical head splits the single input signal light beam into a first incident light and a second incident light, wherein both the first incident light and the second incident light are linearly polarized and perpendicular to each other, *revised*

wherein an original polarizing direction of the first incident light is switched to be a polarizing state perpendicular to the original polarizing direction of the first incident light by passing through a first polarizing state switching mechanism, and an original polarizing direction

Applicati n N .: 09/997,351

Docket No.: JCLA8275

19 of the second incident light is also switched to be a polarizing state perpendicular to the original polarizing direction of the second incident light by passing through a second polarizing state switching mechanism, and the first incident light and the second incident light are transferred from the linear polarizing state to a circular polarizing state, and subsequently focus on the diffraction grating of the optical scale respectively;

24 wherein an angle between the direction of the first incident light and a normal direction of a plane of the diffraction grating is substantially equal to ~~must be sufficiently approximate to a~~ first +1 order diffraction angle of the diffraction grating; a first +1 order diffraction light is generated after incidence, the first +1 order diffraction light is approximately perpendicular to the diffraction grating plane; an angle between the direction of the second incident light and the normal line direction of the diffraction grating plane is substantially equal to a ~~must be~~ approximately enough to the first -1 order diffraction angle of the diffraction grating; on what?

30 wherein the first -1 order diffraction light is generated after being incident, the first -1 order diffraction light is approximately perpendicular to a diffraction grating plane; the first +1 order diffraction light is reversely incident onto the diffraction grating due to after reflection and a second +1 order diffraction light is generated; the second +1 order diffraction light coincides with the first incident light in space but a traveling direction is reverse; the first -1 order diffraction light is perpendicularly incident onto the linear diffraction grating and a second -1 order diffraction light is generated, the second -1 order diffraction light coincides with the second incident light in space but a traveling direction is reverse; after whereby the polarizing states of the second +1 order diffraction light and the second -1 order diffraction light had been changed

Have

Application No.: 09/997,351

D cket No.: JCLA8275

40
 from the circular polarizing state back to the linear polarizing state again, the second +1 order diffraction light travels along the reverse direction of the first incident light, and a first output light beam is output by position shifting; the second -1 order diffraction light travels along a reverse direction of the second incident light and a second output light beam is output by position shifting; and the polarizing direction of the first output light beam is perpendicular to the polarizing direction of the second output light beam, these two output light beams can not be distinguished in space and form a signal light beam; and

47
 a light signal analyzing system, which is used to split the signal light beam, and detects a variation of light intensity; split the signal light beam equally into a first signal light beam and a second signal light beam; further split the first signal light beam into a first orthogonal light beam and a second orthogonal light beam, detect the first orthogonal light beam and the second orthogonal light beam and generate a first orthogonal signal and a second orthogonal signal that have with a phase difference between each other the first orthogonal signal and the second orthogonal signal, whereby a first set orthogonal signal is can be obtained by differentiating the first orthogonal signal and the second orthogonal signal; split the second signal light beam into a third orthogonal light beam and a fourth orthogonal light beam and detects the third orthogonal light beam and the fourth orthogonal light beam to generate a third orthogonal signal and a fourth orthogonal signal that have with a phase difference between each other the third orthogonal signal and the fourth orthogonal, whereby a second set orthogonal signal is can be obtained by differentiating the third orthogonal signal and the fourth orthogonal signal, wherein the first set orthogonal signal and the second set orthogonal signal have a phase difference of 90 degrees.

Application No.: 09/997,351

D cket N .: JCLA8275

Claim 2. (original) The optical automatic control encoder according to claim 1, wherein the diffraction grating in the optical scale is a linear diffraction grating.

Claim 3. (original) The optical automatic control encoder according to claim 1, wherein the diffraction grating in the optical scale is a cylindrical diffraction grating.

Claim 4. (original) The optical automatic control encoder according to claim 1, wherein the diffraction grating in the optical scale is a radiate diffraction grating.

Claim 5. (currently amended) The optical automatic control encoder according to claim 1, wherein the optical head comprises at least:

- 2 → a polarizer, which provides a the polarizing mechanism and a -reflecting mechanism and a transmission mechanism due to the polarizing direction;
- 6 → a right-angle reflector, which provides a reflecting mechanism and a position shifting mechanism;
- 5 → a first quarter-wave plate, which forms the first polarizing state switching mechanism by associating with the right-angle reflector;
- 4 → a first planar reflector, which provides a the reflecting mechanism;
- 3 → a second quarter-wave plate, which forms the second polarizing state switching mechanism by associating with the first planar reflector;

Application No.: 09/997,351

Docket N .: JCLA8275

7 a convex lens, which leads ~~the~~ two parallel lights that are output from the polarizer to the application system, and receives the diffraction light signal that is generated by the diffraction grating;

9/10/01 a third quarter-wave plate, which is located between the polarizer and the convex lens, to rotate the light polarizing state of the first incident light;

10/29/01 a fourth quarter-wave plate, which is located between the polarizer and the convex lens, to rotate the light polarizing state of the second incident light; and

11 a second planar reflector, which provides the reflecting mechanism for the first +1 order diffraction light and the first -1 order diffraction light, and associates with the third quarter-wave plate and the fourth quarter-wave plate to form a third polarizing state switching mechanism and a fourth polarizing state switching mechanism.

Claim 6. (Currently amended) The optical automatic control encoder according to claim 1, wherein the light signal analyzing system comprises:

12 a quarter-wave plate, which transfers the single input signal light beam from a linear polarizing state to the circular polarizing state;

13 a first non-polarizer, which extracts a portion of the single input light beam to form a reference light beam;

a light detector, which receives the reference light beam and provides the signal that is needed for a source light power modulation;

Application N.: 09/997,351

Docket No.: JCLA8275

AY *Amended*

a second non-polarizer, which evenly splits the residual signal light beam that passed through the quarter-wave plate ~~light rotation polarizing element~~, into a first signal light beam and a second signal light beam;

a first polarizer, which evenly splits the first signal light beam into a first orthogonal light beam and a second orthogonal light beam; and

a second polarizer, which evenly splits the second signal light beam into a third orthogonal light beam and a fourth orthogonal light beam.

Claim 7. (original) The optical automatic control encoder according to claim 5, wherein the right-angle reflector includes a corner cube reflector having the silver coated film.

Claim 8. (original) The optical automatic control encoder according to claim 5, wherein each of the first quarter-wave plate and the second quarter-wave plate includes a direct coating film on an exterior of the right-angle reflector.

AS

Claim 9. (currently amended) The optical automatic control encoder according to claim 5, wherein the third quarter-wave plate and the fourth quarter-wave plate are the same in structure as two quarter-wave plates ~~a same quarter-wave plate~~, and the second planar reflector can be put on a center of the quarter-wave plates ~~to simplify the configuration of these two quarter-wave plates and the planar reflector.~~